

# Everyday Life Range Technical Data Sheet

**BRICKWORKS**

Product Range	Product Name	Swatch	State	Length (mm)	Width (mm)	Height (mm)	Dimensional Category	Average Weight / Unit (kg)	Units per Square Metre	Pack Size	Characteristic Unconfined Compressive Strength (f <sub>uc</sub> ) MPa	Maximum Cold Water Absorption (%)	Initial Rate of Absorption (IRA) (kg/m <sup>2</sup> min)	Coefficient of Expansion Factor (mm/m)	Durability Class	Liability to Efflorescence	Lime Pitting Liability	LRV
Everyday Life	Escape		QLD	230	110	76	DW1	2.7	48.5	520	>15	10	0.1-1.0	1.0	Exposure Grade	Slight	Slight	20.3
Everyday Life	Freedom		QLD	230	110	76	DW1	2.7	48.5	520	>15	10	0.1-1.0	1.0	Exposure Grade	Slight	Slight	10.5
Everyday Life	Stimulate QLD		QLD	230	110	76	DW1	2.7	48.5	520	>15	10	0.1-1.0	1.0		Slight	Slight	15

This Data represents average results from commercial production lots.  
 If specific test results are required, sample should be taken from current production lots.  
 AUSTRALIAN STANDARD TEST METHODS AS/NSZ 4456 ARE USED AS APPLICABLE.